


Manual Re-Wind, Hose, Cable & Cord Reels


Pricing Effective: 120109



Visit and download the complete Catalog with latest updates and pricing:
www.trans-motion.com

Model	Hose Capacity	Air/Water Reels	Ht. Wth. Dth	Rating	Wgt #	Price
1115-08-0	150' 3/8" & 1/2"	1/2" Swivel	19",16",18"	300 psi	26	\$415
1116-08-0	250' 3/8", 200' 1/2"	1/2" Swivel	19",18",18"	300 psi	29	477
1117-12-0	50' 3/4	3/4" Swivel	19",16",18"	250 psi	26	431
1118-12-0	75' 3/4	3/4" Swivel	19",18",18"	250 psi	29	495
Model	Hose Capacity	Welding Gas Reels	Ht. Wth. Dth	Rating	Wgt #	Price
1225-04-0	150' Twin 1/4"	Twin 1/4" Swivel	19",16",18"	200 psi	26	\$516
1226-06-0	125' Twin 3/8"	Twin 3/8" Swivel	19",18",18"	200 psi	29	\$550
300 Series	Cable Capacity	Welding Cable Reels	Ht. Wth. Dth	Rating*	Wgt #	Price
1430-0	150' +	Single Reel Design	19",16",18"	to 300 Amps	33	\$635
2432-0	150' + per Spool	2 Spools, Side-By-Side	19",29",18"	to 300 Amps	44	1,133
2434-0	150' + per Spool	2 Spools, Stacked Style	38",16",19"	to 300 Amps	52	1,133
600 Series	Cable Capacity	Welding Cable Reels	Ht. Wth. Dth	Rating*	Wgt #	Price
1460-0	150' +	Single Reel Design	19",16",18"	to 600 Amps	35	\$685
2462-0	150' + per Spool	2 Spools, Side-By-Side	19",29",18"	to 600 Amps	48	1,233
2464-0	150' + per Spool	2 Spools, Stacked Style	38",16",19"	to 600 Amps	56	1,233
Model	Cable Capacity	Power Cable Reels	Ht. Wth. Dth	Rating*	Wgt #	Price
1535-03-0	To 200'	-3- Conductor	19",16",18"	to 35 Amps	32	\$673
1535-04-0	To 200'	-4- Conductor	19",16",18"	to 35 Amps	33	755
1535-05-0	To 200'	-5- Conductor	19",02",18"	to 35 Amps	37	851

1200 Series Welding gas reel



1100, 1225, 1430, 1460



Dual, Combination Reeling Systems

Model #	Configuration	Two Spools*	Ht. Wth. Dth	Hose I.D. or Cable Gauge	Capacity	Wgt #	Price
2714-0	Side-By-Side	Air or Water	19",29",18"	3/8" or 1/2"	200'	45 #	\$830
		Air or Water		3/8" or 1/2"			
2814-0	Stacked	Air or Water	38",16",18"	3/8" or 1/2"	200'	55 #	830
		Air or Water		3/8" or 1/2"			
2712-0	Side-By-Side	Air or Water	19",29",18"	3/8" or 1/2"	200'	45 #	932
		Twin Welding		1/4" or 3/8"			
2812-0	Stacked	Air or Water	38",16",18"	3/8" or 1/2"	200'	55 #	932
		Twin Welding		1/4" or 3/8"			
2735-2-0	Side-By-Side	Air or Water	19",29",18"	3/8" or 1/2"	200'	45 #	1079
		Power Suppy, 35 Amp		12,10, or 8/3			
2835-2-0	Stacked	Air or Water	38",16",18"	3/8" or 1/2"	200'	55 #	1079
		Power Suppy, 35 Amp		12,10, or 8/3			
2735-1-0	Side-By-Side	Twin Welding	19",29",18"	1/4" or 3/8"	200'	45 #	1187
		Power Suppy, 35 Amp		12,10, or 8/3			
2835-1-0	Stacked	Twin Welding	38",16",18"	1/4" or 3/8"	200'	55 #	1187
		Power Suppy, 35 Amp		12,10, or 8/3			

Side-By-Side: 2442 or 2462



Stacked Configurations 2444 or 2464

Quad, Combination Reeling Systems

Model #	Configuration	Four Spools*	Ht. Wth. Dth	Hose I.D. or Cable Gauge	Capacity	Wgt #	Price
2961-0	QUAD	1 Welding Cable	38",28",18"	#2 thru 2/0	200	90#	\$2,164
		2 Welding Cable		#2 thru 2/0			
		3 Welding Gases		1/4"			
		4 Air or Water		3/8" & 1/2"			
2962-0	QUAD	1 Welding Cable	38",28",18"	#2 thru 2/0	200	90#	2321
		2 Welding Cable		#2 thru 2/0			
		3 Air or Water		3/8" & 1/2"			
		4 Power Supply		12,10 or 8/3			
2963-0	QUAD	1 Welding Cable	38",28",18"	#2 thru 2/0	200	90#	2422
		2 Welding Cable		#2 thru 2/0			
		3 Welding Gases		1/4"			
		4 Power Supply		12,10 or 8/3			

Quad Reel, Model 2916-08-125 :
Many Combinations Reels can be created



Storage Reels

Model #	Configuration	Four Spools*	Ht. Wth. Dth	Hose and Cable Capacity	Wgt #	Price
1010-0	Single	1	19",18",18"	To estimate approximate amount of hose or cable that a caddy can handle, refer to capacities listed for single reels above.	30 #	\$399
2010-0	Side-By-Side	2	19",29",18"		40 #	699
2110-0	Stacked	2	38",16",18"		50 #	699
2210-0	Quad	4	38",28",18"		80 #	1239

** Note, Reel capacities can be increase at the factory with a space to make it wider. Call customer service and we will determine what modifications must be made to accommodate your requirement

Working Amps*	Total Feet In Circuit				
	100	150	200	250	300
150	2	2	2	1	2/0
200	1	1	1/0	2/0	3/0
250	1/0	1/0	2/0	3/0	
300	2/0	2/0	3/0		
350	3/0	3/0			
400	3/0	3/0			

* Exceeding the recommended cable length may reduce welding effectiveness